

GC1 150 / 200 / 300 / 600



GC1 150



GC1 200



GC1 300



GC1 600

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC1-150	KP10580-1	150	100	10-16	180	EN60974-13
GC1-200	KP10580-2	200	150	16-25	190	
GC1-300	KP10580-3	300	250	35-50	205	
GC1-600	KP10580-4	600	500	95-120	430	

GC2 250 / 350 / 600



GC2 250



GC2 350



GC2 600

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC2-250	KP10581-1	250	200	25-35	215	EN60974-13
GC2-350	KP10581-2	300	250	50-70	305	
GC2-600	KP10581-3	600	500	95-120	570	

GC3 200 / 300 / 500



GC3 200



GC3 300



GC3 500

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC3-200	KP10582-1	200	150	25-35	190	EN60974-13
GC3-300	KP10582-2	300	250	50-70	350	
GC3-500	KP10582-3	500	400	70-95	550	

GC4 600 – GC5 600 / 800 / 600R



GC4 600



GC5 600



GC5 800



GC5 600R

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC4-600	KP10583-1	600	500	95-120	865	EN60974-13
GC5-600	KP10584-1	600	500	70-95	370	
GC5-800	KP10584-2	800	600	95-120	1650	
GC5-600R (obrotowy)	KP10584-3	600	500	95-120	935	

GC6 600RM



GC6 600RM

GC7 400M / 600M



GC7 400M



GC7 600M

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC6-600RM (obrotowy i magnetyczny)	KP10585-1	600	500	95-120	925	EN60974-13

Zacisk	Indeks	DC@35%	DC@60%	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
GC7-400M (magnetyczny)	KP10586-1	400	300	70-95	755	EN60974-13
GC7-600M (magnetyczny)	KP10586-2	600	500	95-120	1690	

EH1 300 / 500 – EH2 300 / 500



EH1 300



EH1 500



EH2 300



EH2 500

Uchwyt elektrodowy	Indeks	DC@35%	DC@60%	Maks. średnica elektrody	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
EH1-300	KP10575-1	300	200	4-6,3	50-70	470	EN60974-11
EH1-500	KP10575-2	500	400	6,3-10	95-120	600	
EH2-300	KP10576-1	300	200	4-6,3	50-70	430	
EH2-500	KP10576-2	500	400	6,3-10	95-120	580	

EH3 200 / 300 / 400



EH3 200



EH3 300



EH3 400

Uchwyt elektrodowy	Indeks	DC@35%	DC@60%	Maks. średnica elektrody	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
EH3-200	KP10577-1	200	150	2,5-4	25-35	335	EN60974-11
EH3-300	KP10578-1	300	250	4-6,3	50-70	365	
EH3-400	KP10578-2	400	300	5-8	70-95	490	

EH4 300



EH4 300

Uchwyt elektrodowy	Indeks	DC@35%	DC@60%	Maks. średnica elektrody	Przekrój przewodu (mm ²)	Ciężar (g)	Norma
EH4-300	KP10579-1	300	250	4-6,3	50-70	495	EN60974-11