

CRX-25iA





Max. load capacity
at wrist: **25 kg**



Max. reach:
1889 mm

Controlled axes	Repeatability (mm)	Mechanical weight (kg)	Motion range [°]						Maximum speed [°/s] *2						Maximum linear speed (mm/s)	J4 Moment/Inertia (Nm/kgm ²)	J5 Moment/Inertia (Nm/kgm ²)	J6 Moment/Inertia (Nm/kgm ²)
			J1	J2	J3	J4	J5	J6	J1	J2	J3	J4	J5	J6				
6	± 0.05*	127	360	360	540	380	360	450	80	80	120	180	180	180	1000 *1)	100.0/4.70	74.0/4.00	32.0/2.00

Working range



Robot

	CRX-25iA
Robot footprint [mm]	283
Mounting position Floor	•
Mounting position Upside down	•
Mounting position Angle	•



Controller

	R-30iB Plus
Mini Plus	•
Dimensions [mm]	410 x 277 x 370
Tablet TP	•

Electrical connections

Voltage 50/60Hz 3phase [V]	-
Voltage 50/60Hz 1phase [V]	200-230
Average power consumption [kW]	-

Integrated services

Integrated signals on upper arm In/Out	5/6 *3
Integrated air supply	1

Environment

Acoustic noise level [dB]	<70
Ambient temperature [° C]	0-45
Ambient humidity [%]	≤ 75 *4
Ambient humidity - Short term [%RH]	≤ 95 *5
Vibration acceleration [m/s ²]	≤ 4.9 (0.5G)

Protection

Body standard/optional	IP67
Wrist & J3 arm standard/optional	IP67

*1) 2000mm/s in high speed mode

*2) During short distance motions, the speed may not reach the maximum value stated

*3) RS485 interface included

*4) No dew nor frost allowed

*5) Within one month

• standard ○ on request - not available () with hardware and/or software option

*Based on IS09283